

**1. IDENTIFICATION OF THE PREPARATION AND COMPANY**  
**SAFETY DATA SHEET**

***Vinyl Master***

**W.R.DAY LTD.**  
6 MANOR INDUSTRIAL ESTATE

COMEYTROWE  
TAUNTON TA4 1EF

Issue No: RE05/04

Date: 05/10/05

TEL. +44(0)1823 276506/7

FAX +44(0)1823 336336

INTERNET : www.autoday.com

Page 1 of 2

**2. COMPOSITIONAL INFORMATION**

HAZARDOUS INGREDIENTS:

Petroleum Distillate

FLAMMABLE

60-100%

**3. HAZARDS IDENTIFICATION**

MAIN HAZARD : FLAMMABILITY

SPECIFIC HAZARDS : Prolonged skin contact may cause defatting and dryness.

Eye contact will result in severe irritation.

Ingestion will cause stomach upset.

Inhalation may cause dizziness/nausea especially in confined areas.

**4. FIRST AID MEASURES**

SKIN : Wash with clean water.

EYES : Flush with water for 15 minutes. If irritation persists seek medical aid.

INGESTION : Give water to drink. Seek immediate medical advice.

INHALATION : Remove casualty from exposure. Summon immediate medical aid.

**5. FIRE FIGHTING MEASURES**

PRODUCTS OF COMBUSTION : Oxides of carbon, hydrogen and sulphur.

EXTINGUISHING AGENTS : Carbon dioxide, dry powder or chemical foam.

PRECAUTIONS : Wear self-contained breathing apparatus.

**6. ACCIDENTAL RELEASE MEASURES**

Large spillages extremely unlikely.

Eliminate all sources of ignition. Do not allow entry into rivers / drains.

Absorb using sand or earth.

**7. HANDLING AND STORAGE**

Store at temperature between 0DegC and 20DegC.

Keep out of reach of children.

Store in original containers in a cool, dry place.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Effects of over-exposure:**

Skin Contact : Prolonged contact will cause defatting and dryness.

Eye Contact : Irritation and redness.

Ingestion : Stomach upset.

Inhalation : May cause dizziness / nausea.

**Personal Protection:**

Good industrial hygiene is usually sufficient but if splashing likely wear suitable eye/face protection.

Do not ingest.

Ensure adequate ventilation when using product.

Refer to Section 2 and HSE Guidance Note EH40 to establish current OEL / MEL values.

***Vinyl Master***

Issue No : RE05/04

Date : 05/10/05

Page 2 of 2

**9. PHYSICAL & CHEMICAL PROPERTIES**

Appearance : Clear mobile liquid  
Odour : Perfumed  
pH : n.d.  
Relative Density : 0.8 @ 20DegC  
Boiling Point : >100DegC  
Freezing Point : <0DEGC  
Flash Point : Between 21 and 55DegC  
Miscible with most organic solvents

**10. STABILITY AND REACTIVITY**

Product is stable. Avoid extremes of temperature. Do not mix with any other product.  
Product does not decompose.

**11. TOXICOLOGICAL INFORMATION**

ORAL LD50 : >2000mg/kg (Species : Oral, Rat – calculated).  
Acute (short-term) effects : Dizziness / nausea if inhaled in confined space.  
Chronic (long-term) effects : Prolonged contact can cause skin defatting / dryness and increased susceptibility to dermatitis.  
Refer to HSE Guidance Note EH40 to establish current OEL/MEL values.

**12. ECOLOGICAL INFORMATION**

Product unlike to constitute a bio or eco hazard.  
Product is not biodegradable.  
Bioaccumulation not expected.

**13. DISPOSAL CONSIDERATONS**

Absorb spilled material using sand or earth. Dispose as solid waste in accordance with local and national regulations.

**14. TRANSPORT INFORMATION**

UN Substance ID : 1993

**15. REGULATORY INFORMATION**

RISK PHRASES :  
R10 : FLAMMABLE  
SAFETY PHRASES :  
S2 : Keep out of reach of children.  
S46 : If swallowed do not induce vomiting. Seek medical advice immediately and show this container or label.

**16. OTHER INFORMATION**

Refer to product label for detailed instructions for use. The information in this Data Sheet is to be used in conjunction with the information on the product label. It is the responsibility of employers to ensure that all persons using or handling this product have access to and are aware of the information contained herein. Possession of this Data Sheet does not in itself constitute compliance with the HSAW Act or COSHH Regulations.