

**1. IDENTIFICATION OF THE PREPARATION AND COMPANY**  
**SAFETY DATA SHEET**

***Autodash***

Issue No: AE06/03

Date: 13/07/03

Page 1 of 2

**W.R.DAY LTD.**  
6 MANOR INDUSTRIAL ESTATE

COMEYTROWE  
TAUNTON TA4 1EF

TEL. +44(0)1823 276506/7  
FAX +44(0)1823 336336  
INTERNET : www.autoday.com

**2. COMPOSITIONAL INFORMATION**

**HAZARDOUS INGREDIENTS:**

Low boiling point modified naphtha – naphtha (petroleum) solvent refined light

CAS: 64741-84-0 EINECS: 265-086-6 In neat form: F(R11); Xi (R38); N (R51/53); R67 1-10%

**3. HAZARDS IDENTIFICATION**

**MAIN HAZARDS :** Extremely flammable. Harmful to aquatic organisms. May cause long-term adverse effects in aquatic environment.

**OTHER HAZARDS :** In use may form flammable/explosive vapour-air mixture.

**4. FIRST AID MEASURES**

**SYMPTOMS:**

**SKIN:** May be irritation and redness at point of contact.

**EYES:** May be irritation and redness. Corneal burns may occur.

**INGESTION:** Possible nausea and stomach pain. May be vomiting and diarrhoea. May be loss of consciousness. Convulsions may occur.

**INHALATION:** Exposure may cause coughing/wheezing. May be lung congestion causing shortness of breath. May be loss of consciousness. Convulsions may occur.

**ACTION:**

**SKIN :** Remove contaminated clothing and wash with clean water. Seek medical aid if symptoms persist.

**EYES :** Flush with water for 15 minutes. Seek medical aid.

**INGESTION :** Do not induce vomiting. Give water to drink. Seek immediate medical advice.

**INHALATION :** Remove casualty from exposure. If unconscious check breathing and apply artificial respiration if necessary. If breathing OK place in the recovery position. If conscious ensure casualty is lying down. If breathing becomes bubbly have casualty sit and provide oxygen if available. Summon immediate medical aid.

**5. FIRE FIGHTING MEASURES**

**EXPOSURE HAZARDS :** Extremely flammable. Vapour may travel to source of ignition and flash back.

**EXTINGUISHING AGENTS :** Carbon dioxide, alcohol resistant foam.

**PRECAUTIONS :** Wear self-contained breathing apparatus and protective clothing.

**6. ACCIDENTAL RELEASE MEASURES**

Eliminate all sources of ignition. Do not allow entry into rivers/drains. Absorb with inert absorbent.

**7. HANDLING AND STORAGE**

Store in cool well-ventilated area.

Keep away from sources of ignition.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Engineering measures:** Ensure adequate ventilation. Ensure lighting and electrical equipment are not sources of ignition.

**Personal Protection:**

If skin splashes are likely uses gloves or barrier cream.

Wear suitable protective eye goggles.

Do not ingest.

Ensure adequate ventilation when using product.

Refer to Section 2 and HSE Guidance Note EH40 to establish current OEL / MEL values.

**Autodash**

Issue No : AE06/03

Date : 13/07/03

Page 2 of 2

**9. PHYSICAL & CHEMICAL PROPERTIES**

State : Aerosol  
Appearance : Colourless  
Odour : Characteristic  
Evaporation rate : Fast  
Oxidising : Non-oxidising (by EC criteria)  
Flash Point : -44DegC  
Solubility in water : Insoluble

**10. STABILITY AND REACTIVITY**

Product is stable under normal conditions. Avoid flames and sources of ignition. Avoid oxidising agents. In combustion emits toxic fumes of carbon dioxide and carbon monoxide.

**11. TOXICOLOGICAL INFORMATION**

Ingredient : LOW BOILING POINT MODIFIED NAPHTHA – NAPHTHA (PETROLEUM) SOLVENT REFINED LIGHT //eco

**12. ECOLOGICAL INFORMATION**

Mobility : Insoluble in water Absorbed only slowly into soil.  
Persistence and degradability : No data available  
No bioaccumulation data available.  
Other hazards : Harmful to aquatic organisms

**13. DISPOSAL CONSIDERATIONS**

Dispose in accordance with local, national and international regulations.

**14. TRANSPORT INFORMATION**

<b>ADR/RID</b>	UN No : 1950	ADR Class: 2
	Labelling 2.1	Shipping Name : Aerosols
<b>IMDG/IMO</b>	UN No 1950	Class: 2
	EmS: 2-13	Labelling: 2.1
<b>IATA/ICAO</b>	UN No : 1950	Class: 2
	Labelling : 2.1	

**15. REGULATORY INFORMATION**

SYMBOL: EXTREMELY FLAMMABLE  
RISK PHRASES :  
R11 : EXTREMELY FLAMMABLE  
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
SAFETY PHRASES :  
S16 : Keep away from sources of ignition – No Smoking  
S23 : Do not breathe aerosol.  
S51 : Use only in well-ventilated areas.

**16. OTHER INFORMATION**

Refer to product label for detailed instructions for use. The information in this Data Sheet is to be used in conjunction with the information on the product label. It is the responsibility of employers to ensure that all persons using or handling this product have access to and are aware of the information contained herein. Possession of this Data Sheet does not in itself constitute compliance with the HSAW Act or COSHH Regulations.  
Information herein is believed to be correct but does not purport to be all inclusive and should be used only as a guide. This Company shall not be held liable for any damage resulting from handling or from contact with this product.